



Date: 14.04.2026

Grain d.o.o.  
Letalska cesta 32j, SI-1000 Ljubljana

VAT ID: SI94632006

Phone: +386 59 251 017

E-mail: [info@grain.si](mailto:info@grain.si)

WWW: [www.mail.print-materials.staging.digitalist.si](http://www.mail.print-materials.staging.digitalist.si)



(image is symbolic)

## Laser film PET Optimont LF 320 x 480 mm

Category: [Laser Film](#)

Availability: **estimated time of delivery 15.04.2026**

code: **389**

**Price: 70,53€**

### Technical specifications

Thickness: 95 mic  
Quantity: 100 pcs  
Size: 320 x 480 mm

### Short description

PET film biaxially oriented, translucent, heat-resistant and positive film for laser printers.

**Scalable PET film, biaxially oriented, 2-sided white matt coating, translucent, dimensionally stable, as positive film for the laser printer. The film has a copyable, antistatic surface with uniform print quality, suitable for all toner-based printing systems, as well as for all plotters and can be used for hand marking with commercially available pens.**

**All optimont® laser films are made of heat-resistant BOPET (biaxially oriented PET).**

**Matt coated optimont® laser film, which was originally developed specifically for positive film production, is now used in design, labeling and backlight applications for digital printing. The film has a copyable, antistatic surface with uniform print quality and toner coverage. It can be used on all toner-based printing systems as well as on all plotters and for manual marking with standard pens. The optimont laser films have a temperature resistance up to 140°C (short term up to 200°C).**